

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 633 678 B1

(12) EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
19.07.2000 Bulletin 2000/29

(51) Int. Cl.<sup>7</sup>: H04L 12/18, H04L 12/56

(21) Application number: 93201896.3

(22) Date of filing: 29.06.1993

(54) Resequencing method and resequencing device realizing such a method

Verfahren und Gerät für sequentielle Rückordnung

Procédé et dispositif pour la remise en séquence

(84) Designated Contracting States:  
BE DE ES FR GB IT NL SE

(43) Date of publication of application:  
11.01.1995 Bulletin 1995/02

(73) Proprietor: ALCATEL  
75008 Paris (FR)

(72) Inventor:  
Peschl, Robert Nicolas Louis  
B-1040 Schaerbeek (BE)

(74) Representative:  
Narmon, Gisèle Marie Thérèse et al  
Alcatel Bell N.V.  
Intellectual Property Department  
Francis Wellesplein 1  
2018 Antwerpen (BE)

(56) References cited:

- COMPUTER NETWORKING SYMPOSIUM April 1988, WASHINGTON, USA pages 79 - 81 I. GOPAL ET AL. 'Multicasting to Multiple Groups over Broadcast Channels'
- MEDITERRANEAN ELECTROTECHNICAL CONFERENCE vol. 1, May 1991, NEW YORK, USA pages 505 - 508 C. SA DA COSTA ET AL. 'SEQUENCE NUMBER SYNCHRONIZATION IN THE ATM ADAPTATION LAYER'
- PATENT ABSTRACTS OF JAPAN vol. 005, no. 011 (E-042)23 January 1981 & JP-A-55 140 347 (OKI ELECTRIC INC. CO. LTD.) 1 November 1980
- IEEE COMMUNICATIONS MAGAZINE vol. 26, no. 4, April 1988, NEW YORK, US pages 9 - 14 C.H. HEMRICK ET AL. 'Switched Multimegabit Data Service and Early Availability via MAN Technology'

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 633 678 B1

## Description

[0001] The present invention relates to a method for resequencing information packets of an information packet stream transmitted from a transmitter station to a receiver station over a network and identified by sequence numbers.

[0002] Such a method is well known in the art, e.g. from the Euro-PCT Application No. 438415 (Henrion 17) Therein, the network is a multipath self routing switch, so that packets may follow different paths therein and may therefore be out of sequence upon their arrival in the receiver station. In this station the packets are then resequenced based on sequence numbers constituted by time stamps allocated to them in the transmitter station.

[0003] This known resequencing method is however not applicable when the information packet stream comprises two or more types of intermixed packets which have to be in sequence in the receiver station, not only within each type they belong to but also with respect to each other. This is for instance the case with a so called Switched Multimegabit Data Service (SMDS) network as described in the Bellcore specifications TR-TSV-000772 (corresponding CCITT Draft Recommendation I364, Geneva, June 1992 or ETSI final draft pr ETS 300217 September 1992 ) and wherein packets belonging to a same information stream also called session or message can be transmitted either as first packets with group addresses from the transmitter station to a plurality of receiver stations, including a predetermined receiver station, via arbitrary paths, which means that they can be received out of sequence in the latter receiver station, or as second packets with individual addresses from the transmitter station to the predetermined receiver station where they are then received in sequence. As all these packets, i.e. as well the first as the second ones, belong to a same information stream, the first packets have to be resequenced in the predetermined receiver station to be in sequence not only with respect to themselves, but also with respect to the second packets. Resequencing these first and second packets with the help of sequence numbers or time stamps allocated thereto as in known systems has the important drawback that it is impossible to know upon receipt of a sequence of first and second packets whether packets have been lost, and thus whether one has to wait for those possibly lost packets.

[0004] Indeed, the transmitter station which is not aware to which message a packet belongs, has to sequentially allocate sequence numbers/time stamps to the packets it sends out, without taking into account to which message these packets belong. As a result, the packets received by a receiver station are not numbered consecutively because first packets are sent to all receiver stations, while second packets are sent to specific ones. Considering for instance a transmitter station which has to send 10 packets numbered 1 to 10 of

which packets 1 to 3 are first packets, 4 to 6 are second packets intended for a receiver station Ra, 7 and 8 are second packets intended for Rb and 9 and 10 are first packets, Ra then receives packets 1 to 6, 9 and 10 and Rb receives packets 1 to 3, and 7 to 10. The packets received are thus not numbered consecutively and it is impossible for the receiver stations to know whether the gaps in the numbering are due to packet loss or not.

[0005] To be noted that the above reasoning is also applicable to time stamps.

[0006] The same problem but related to multicasting is described in the article "Multicasting to Multiple Groups over Broadcast Channels" by Gopal et al, pages 79-81 of the Computer Networking Symposium papers (April 1988, Washington, USA).

[0007] The solutions proposed therein rely on the inclusion of additional information in the message stream to indicate to every destination the sequence numbers of the messages destined to it, which obviously imply an increase of overhead bandwidth, thus negatively influencing the bandwidth available for transmission of data.

[0008] An object of the present invention is to provide a resequencing method of the above known type but which is more particularly applicable when the information packet stream includes first packets which may be received in said receiver station out of sequence with respect to each other or with respect to second packets which are always received in sequence, and which has not got the above mentioned drawback.

[0009] According to the invention, this object is achieved due to the fact that in the latter case said method includes the steps of :

- in said transmitter station, allocating predetermined first sequence numbers to said first packets and allocating to each second packet following a first packet a second sequence number which is related according to a predetermined relation to the predetermined first sequence number allocated to this first packet; and
- in said receiver station, resequencing said first and second packets according to their first and second sequence numbers respectively.

[0010] By linking the sequence numbers of the first and the second packets, and allocating predetermined first sequence numbers to the first packets an easy resequencing is possible and a receiver station always knows whether, upon receipt of a packet, it has to wait for a previous one not yet received.

[0011] Further characteristics of the invention are that said allocated predetermined first sequence numbers form an increasing/decreasing monotonous series and that said second sequence number allocated to said second packet is equal to the predetermined first sequence number of the first packet preceding said second packet.

[0012] This choice of the predetermined first sequence numbers and of the predetermined relation makes the resequencing even easier due to this simple relationship between the first packets with respect to each other and between the first and the second packets.

[0013] Known resequencing devices realizing the known resequencing methods are obviously restricted in the same way as described above with relation to the known resequencing methods.

[0014] The present invention therefore also relates to a resequencing device for resequencing information packets of an information packet stream transmitted from a transmitter station to a receiver station over a network and identified by sequence numbers characterized in that, when said information packet stream includes first packets which may be received in said receiver station out of sequence with respect to each other or with respect to second packets which are always received in sequence, said resequencing device includes :

- a sequence number allocation means located in said transmitter station and which is able to allocate predetermined first sequence numbers to said first packets and to allocate to each second packet following a first packet a second sequence number which is related according to a predetermined relation to the predetermined first sequence number allocated to this first packet; and
- a resequencing means located in said receiver station and which is able to resequence said first and second packets according to their first and second sequence numbers respectively, which realizes the new resequencing method.

[0015] The above mentioned and other objects and features of the invention will become more apparent and the invention itself will be best understood by referring to the following description of an embodiment taken in conjunction with the accompanying drawing representing a communication system which includes a resequencing device C1, P1, B, P2, C2, T according to the present invention and which realizes a resequencing method also according to the present invention.

[0016] This communication system includes a Switched Multimegabit Data Service network SMDS to which 4 user terminals U1 to U4 are coupled via respective identical interworking units IWU1 to IWU4 of which only IWU1 and IWU2 are partly represented in detail. More specifically of IWU1 a segmenting circuit S for segmenting a message Min received from U1, a processing circuit P1 and a counter circuit C1 are shown, and of IWU2 a processing circuit P2 is shown together with a counter module C2, a buffering module B, a timer circuit T and a reassembly circuit R for reassembling packets Pin received from P2, into a message Mout destined for U2.

[0017] C1 and P1 together constitute a sequence number allocation circuit and P2, C2, B and T are part of a resequencing circuit, both circuits constituting a sequencing device.

[0018] C1 and C2 are wrap-around counters, i.e. counters which after having reached a maximum value automatically restart counting from their initial value.

[0019] P1 and P2 control C1 and C2 respectively and retrieve respective counter values therefrom.

[0020] P2 is additionally connected to B and T by means of bidirectional links.

[0021] S passes to P1 packets obtained by segmenting a message Min and in response P1 generates outgoing packets Pout for transfer over SMDS. Therein these packets are routed to e.g. IWU2 where they are received by P2 as incoming packets Pin. The latter are after processing and possible buffering passed to R for reassembly into Mout.

[0022] C1, S, P1, B, P2, R, T and C2 are not described in further detail because, for a person skilled in the art, their realization is obvious from their following functional description.

[0023] Packets belonging to a same message or information flow can be transmitted over SMDS in two ways, i.e. as packets of a first type, hereafter called first packets, having a group destination address and which are sent to all interworking units belonging to a corresponding group, e.g. IWU1 to IWU4 and as packets of a second type, hereafter called second packets, having an individual destination address and which are transmitted from point to point, e.g. from IWU1 to IWU2. Individual address packets or second packets are hereafter indicated by Ix where x is the sequence number of the packet in the message it belongs to, and in the same way group address packets or first packets are called Gx.

[0024] It has to be noted that the counter module C2 includes as many counter circuits as there are interworking units which can send first packets to it, but for simplicity reasons it is assumed that C2 only includes a single counter circuit allocated to the first packets received from IWU1. Extension to a counter module with a plurality of counter circuits is obvious to a person skilled in the art.

[0025] P1 sets C1 to an initial value, e.g. 0, at start-up of the sequence allocation circuit. Whenever a packet is afterwards received from S for transmission over SMDS, P1 gets the current counter value provided by C1 and assigns it to that packet when it is a second packet. On the contrary, when the received packet is a first packet then P1 increments C1 by a predetermined value, e.g. 1, and assigns the thus obtained value to that packet. As a result, second packets always have the same sequence number as the preceding first packet, except for second packets sent immediately after start-up of the sequence allocation circuit. These packets indeed have sequence number 0 whilst there is no preceding first packet with value 0.

[0026] At the receiving side, e.g. IWU2, and upon start-up of the resequencing circuit, C2 is set by P2 to the initial value of C1 by means of a synchronization scheme. Synchronization schemes as the one used in this embodiment are well known in the art and therefore the used scheme is not described in detail. As will become clear from the following, the value of C2 at a given instant in time indicates the sequence number of the first packet which was the last one to be passed to R, and its value incremented by 1 indicates which first packet is expected to be received next.

[0027] To be noted that the maximum value of C1 and C2 at which the wrap-around occurs has to be the same one for both and that this maximum value has to be chosen in such a way, that the receiver station never has to process two or more first packets with the same sequence number at the same time.

[0028] When a packet Pin is received in IWU2, P2 compares its sequence number with the current counter value provided by C2.

[0029] If this sequence number is higher than the value of C2, in case of a second packet, or than the value of C2 incremented by 1 when a first packet is received, then P2 stores the packet Pin in B because this means that as well in case of a first packet as in case of a second packet at least one preceding first packet has still to be received. Obviously, the number of first packets still to be received depends on the difference between the value of C2 + 1 and the sequence number of the received packet. In other words, the number of still expected packets is equal to the sequence number of the received packet minus the value of C2 + 1.

[0030] P2 starts a timer, by using T, for each buffered packet. When one of these timers expires it is supposed that all still to be received first packets with sequence number smaller than the sequence number of the packet for which that timer was started are lost and the packet for which the timer has expired is together with all buffered first packets having a sequence number lower than that for which the timer has expired and with all related buffered second packets sequenced in the following way before transmission to R : all packets are ordered in ascending order, with the second packets interleaved with the first packets in such a way that the second packets always follow the first packets with the same sequence number if present and that the sequence of receipt of the second packets is preserved. C2 is then set by P2 to a value equal to the sequence number of the packet of which the timer has expired. The reason for this procedure is that according to a requirement of the system the packets may not stay in the system for longer than a predefined time interval equal to the maximum transmission delay.

[0031] If the received packet is a first packet and its sequence number is equal to the counter value C2 + 1, P2 checks if there are buffered packets. If so, all buffered first packets the sequence numbers of which, with

the sequence number of the received packet, form an increasing series with increment value one are retrieved from the buffer together with all second packets having a sequence number equal to the sequence number of the received packet or of one of the retrieved packets. All these packet are then ordered as described earlier. Each time a first packet is passed to R, P2 increments C2 by one and cancels a possible timer started for that packet. If no packets are buffered or if the buffered first packets do not form the mentioned increasing series with the received packet, only the latter is passed to R and C2 is incremented by 1. It has then to be checked whether there are no buffered second packets which have then to be retrieved and passed to R in the sequence they were received.

[0032] Upon receipt of a second packet with sequence number equal to the value of C2, P2 passes this packet to R, since this means that the preceding first packet was already received and passed to R.

[0033] Packets received by P2 and having a lower sequence number than the value of C2 in case of second packets or than the value of C2 + 1 in the case of first packets are discarded. This is correct since in case of a second packet this means that the packet was overtaken by a first packet, whereas in the case of a first packet this means that the received packet was supposed to be lost due to a previous time out.

[0034] To illustrate the above described procedure it is now applied to a transmitted packet stream I0, I0, G1, G2, G3, I3, I3, G4, G5, G6, I6, I6, I6, G7, I7 which is after start-up of the resequencing circuit received by P2 as I0, G1, I0, G2, G3, I3, I3, G5, G4, I6, I6, G6, I6, G7, I7.

[0035] After a generally known synchronization procedure C2 is set to an initial value of 0 by P2. Upon receipt of I0 by P2, the latter transmits I0 to R. When G1 is received its sequence number is compared with the value of C2 which is 0. This indicates that the next to be received first packet has to have sequence number one and consequently G1 is passed to R. Thereafter it is checked if there are no buffered packets, and C2 is incremented to 1, which means that the next expected first packet has sequence number 2. The following packet I0 is discarded because it has a sequence number lower than the value of C2 and was thus overtaken by G1. G2 has a sequence number corresponding to the next to receive sequence number and is thus passed by P2 to R. Thereafter B is checked for possible buffered packets, and C2 is incremented to 2. The same applies to G3 and C2 is incremented to 3. The two following packets I3, I3 are second packets the sequence number of which is equal to the value of C2 which means that the preceding first packet had sequence number 3 and as a consequence the packets are passed to R. When G5 is received P2 detects that it is not the following expected first packet which has a sequence number equal to the value of C2 + 1 = 4. G5 is therefore buffered and a timer is started for G5 by T

under control of P2. It is assumed that G4 is received before the timer has reached a predetermined value corresponding to the maximum transmission delay in the network. Since the sequence number of G4 corresponds to the value of the next expected first packet, i.e.  $C2 + 1$ , P2 checks if there are packets buffered and retrieves G5 from B. The timer is stopped and the received and the retrieved packets are sequenced as G4, G5 and transmitted to R, whilst C2 is twice incremented to become 5. Had the timer expired before G4 was received, then G4 would have supposed to be lost and G5 would have been retrieved from B and transmitted to R and C2 would then have put equal to 5 by P2.

[0036] When the packets I6, I6 are received, P2 detects that these are second packets and thus should have a sequence number corresponding to the value of C2, i.e. 5. Since this is not true and because their sequence number is higher, they are buffered and G6 is expected. Upon receipt of G6, P2 finds out it is a first packet which should have the value of  $C2 + 1$ , i.e. 6. Since this is the case P2 checks if there are no packets buffered, retrieves I6, I6 from B and sends the packets to R in the sequence G6, I6, I6. C2 is incremented to 6. The then received packet I6 is passed to R because C2 equals 6. Since C2 has value 6, P2 expects as following first packet G7, which is therefore passed to R. It is checked whether there are packets buffered and C2 is incremented. I7 is then passed to R because its sequence number has the same value as C2, which means that a previous first packet with sequence number 7 was received.

[0037] It has to be noted that the above method can be applied in a similar way when the increment value is greater than 1, or for decrements with a predetermined value. Also another relationship can be chosen between the sequence numbers of the second packets and the preceding first packet.

[0038] It has also to be noted that, since messages can also be transmitted from IWU2 to IWU1, a sequence allocation circuit and a resequencing circuit such as those of IWU1 and IWU2 are also present in IWU2 and IWU1 respectively.

#### Claims

1. Method for resequencing information packets of an information packet stream (Min) transmitted from a transmitter station (IWU1) to a receiver station (IWU2) over a network (SMDs) and identified by sequence numbers, characterized in that, for first packets included in said information packet stream (Min) and received in said receiver station (IWU2) out of sequence with respect to each other or with respect to second packets which are always received in sequence, said method includes the steps of :

- in said transmitter station (IWU1), allocating

predetermined first sequence numbers to said first packets and allocating to each second packet following a first packet a second sequence number which is related according to a predetermined relation to the predetermined first sequence number allocated to this first packet; and

- in said receiver station (IWU2), resequencing said first and second packets according to their first and second sequence numbers respectively.

2. Method according to claim 1, characterized in that said predetermined first sequence numbers allocated to said first packets form an increasing/decreasing monotonous series.
3. Method according to claim 1, characterized in that said second sequence number allocated to said second packet is equal to the predetermined first sequence number of the first packet preceding said second packet.
4. Method according to claims 2 and 3, characterized in that a second packet is discarded in said receiver station (IWU2) when its said second sequence number is smaller/greater than the predetermined first sequence number of a previously received first packet.
5. Method according to claims 2 and 3, characterized in that received second packets which have a same second sequence number which is larger smaller than the predetermined first sequence number of the previously received first packet are buffered until receipt of a first packet having a predetermined first sequence number equal to the second sequence number of the thus buffered second packets.
6. Method according to claims 2 and 3, characterized in that upon receipt in said receiver station (IWU2) of one of said first packets from said transmitter station (IWU1) said first packet is buffered when its predetermined first sequence number is larger/smaller than the sequence number of the last previously received and not buffered packet incremented/decremented by a predetermined value, that upon receipt by said receiver station (IWU2) of one of said second packets from said transmitter station (IWU1), said second packet is buffered when its second sequence number is larger/smaller than the sequence number of the last previously received and not buffered packet, that upon receipt by said receiver station (IWU2) of a second packet with a said second sequence number equal to the sequence number of the last previously received and not buffered packet or of a first packet with a

said predetermined sequence number equal to the sequence number of the last previously received and not buffered packet incremented/decremented by said predetermined value, said packet is passed to an output terminal (R) of said receiver station (IWU2), those already buffered first packets, the first sequence numbers of which together with the sequence number of the passed first packet form part of said monotonous series also being passed to said output terminal (R), in ascending/descending order of their first sequence number, together with those second packets having a said second sequence number equal to a previously passed packet, and that upon receipt of a said second packet having a said second sequence number smaller/larger than the sequence number of the last previously received and not buffered packet or of a first packet having a predetermined first sequence number smaller/larger than the sequence number of the last previously received and not buffered packet incremented/decremented by said predetermined value, said packet is discarded.

7. Method according to claim 6, characterized in that a timer is started for each one of said buffered packets, all buffered packets with sequence number smaller/greater than the sequence number of said one packet, and all buffered packets with sequence number greater/smaller than the sequence number of said one packet and which form with said one packet part of said monotonous series, being passed to said output terminal (R) after having been sequenced to form a series of packets related to said monotonous series in a predetermined way, when said timer (T) reaches a predetermined value.
8. Method according to claim 1, characterized in that in said network (SMDS) said second packets have an individual destination address and are sent from said transmitter station (IWU1) to said receiver station (IWU2) and said first packets have a group destination address and are sent from said transmitter station (IWU1) to said receiver station (IWU2) and to at least one other receiver station (IWU3, IWU4).
9. Method according to claim 1, characterized in that a predetermined initial value is assigned to the second sequence number of all second packet which are transmitted before the transmission of any first packet.
10. Resequencing device for resequencing information packets of an information packet stream (Min) transmitted from a transmitter station (IWU1) to a receiver station (IWU2) over a network (SMDS) and identified by sequence numbers characterized in that, for first packets included in said information packet stream (Min) which are received in said

receiver station (IWU2) out of sequence with respect to each other or with respect to second packets which are always received in sequence, said resequencing device includes :

- a sequence number allocation means (P1, C1) located in said transmitter station (IWU1) and which is adapted to allocate predetermined first sequence numbers to said first packets and to allocate to each second packet following a first packet a second sequence number which is related according to a predetermined relation to the predetermined first sequence number allocated to this first packet; and
  - a resequencing means (P2, B, C2, T) located in said receiver station (IWU2) and which is adapted to resequence said first and second packets according to their first and second sequence numbers respectively.
11. Resequencing device according to claim 10, characterized in that said predetermined first sequence numbers allocated to said first packets form an increasing/decreasing monotonous series.
  12. Resequencing device according to claim 10, characterized in that said second sequence number allocated to said second packet is equal to the predetermined first sequence number of the first packet preceding said second packet.
  13. Resequencing device according to claims 11 and 12, characterized in that said sequence number allocation means (P1, C1) includes a counter means (C1) adapted to provide a counter value and a processing means (P1) which is adapted to assign said counter value to said second packets to be transmitted and is adapted to control said counter means to be incremented/decremented by a predetermined value before assigning said counter value to said first packets to be transmitted.
  14. Resequencing device according to claims 11 and 12, characterized in that said resequencing means (P2, B, C2, T) includes a buffering means (B) adapted to buffer received second packets having a same second sequence number which is larger/smaller than the sequence number of the last previously received and not buffered packet until receipt of a first packet having a predetermined first sequence number equal to the second sequence number of the thus buffered second packets.
  15. Resequencing device according to claims 13 and 14, characterized in that said resequencing means (P2, B, C2, T) includes at least one second counter means (C2) providing a second counter value the initial value of which is at start-up of said resequencing device.

quencing means made equal to the initial value of said first counter (C1) and a second processing means (P2) which, upon receipt of one of said first packets from said transmitter station (IWU1), is adapted to buffer said first packet in said buffering means (B) when its predetermined first sequence number is larger/smaller than said second counter value incremented/decremented by said predetermined value, which, upon receipt of one of said second packets from said transmitter station (IWU1), is adapted to buffer said second packet in said buffering means (B) when its second sequence number is larger/smaller than said second counter value, which, upon receipt of a second packet with a second sequence number equal to said second counter value or of a first packet with a predetermined first sequence number equal to said second counter value incremented/decremented by said predetermined value, is adapted to pass said packet to an output terminal (R) of said resequencing means and to control said second counter means (C2) to be incremented/decremented by said predetermined value when a said first packet is passed to said output terminal (R), those already buffered first packets the first sequence numbers of which together with the first sequence number of the first passed packet form part of said monotonous series and those second packets having a second sequence number equal to the sequence number of either the passed or of one of those buffered first packets then also being passed to said output terminal (R) in such a way that those buffered first packets are sequenced in ascending/descending order of their sequence number, together with buffered second packets sequenced in such a way with respect to said passed first packets that they follow a first packet having the same predetermined first sequence number as their own second sequence number, and which, upon receipt of a second packet having a second sequence number smaller/larger than said counter value or of a first packet having a predetermined first sequence number smaller/larger than said counter value incremented/decremented by said predetermined value, is adapted to discard said packet.

16. Resequencing device according to claim 15, characterized in that said resequencing means includes a timer means (T), controlled by said second processing means (P2), adapted to start a timer for each one of said buffered packets, all buffered packets with sequence number smaller/greater than the sequence number of said one packet, and all buffered packets with sequence number greater/smaller than the sequence number of said one packet and which form with said one packet part of said monotonous series, being passed to said output terminal (R) after having been

sequenced to form a series of packets related to said monotonous series in a predetermined way, when said timer reaches a predetermined value.

17. Resequencing device according to claim 10, characterized in that in said network (SMDS) said second packets have an individual destination address and are sent from said transmitter station (IWU1) to said receiver station (IWU2) and said first packets have a group destination address and are sent from said transmitter station (IWU1) to said receiver station (IWU2) and to at least one other receiver station (IWU3, IWU4).

#### 15 Patentansprüche

1. Verfahren zum sequentiellen Rückordnen von Informationspaketen eines Informationspaketstromes (Min), der über ein Netz (SMDS) von einer Sendestation (IWU1) zu einer Empfangsstation (IWU2) gesendet wird und durch Sequenznummern identifiziert ist, dadurch gekennzeichnet, daß für erste Pakete, die im Informationspaketstrom (Min) enthalten sind und in der Empfangsstation (IWU2) nicht mehr sequentiell geordnet empfangen werden, und zwar bezüglich zueinander oder bezüglich zweiter Pakete, welche immer sequentiell geordnet empfangen werden, das Verfahren folgende Schritte beinhaltet:
  - in der Sendestation (IWU1) werden vorbestimmte erste Sequenznummern den ersten Paketen zugeordnet und jedem auf ein erstes Paket folgenden zweiten Paket eine zweite Sequenznummer zugeordnet, welche zur diesem ersten Paket zugewiesenen vorbestimmten ersten Sequenznummer eine vorbestimmte Beziehung besitzt; und
  - in der Empfangsstation (IWU2) werden die ersten und zweiten Pakete gemäß ihrer ersten bzw. zweiten Sequenznummern sequentiell rückgeordnet.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die den ersten Paketen zugeordneten vorbestimmten ersten Sequenznummern eine zunehmende/abnehmende monotone Reihe bilden.
3. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die dem zweiten Paket zugeordnete zweite Sequenznummer gleich der vorbestimmten ersten Sequenznummer des dem zweiten Paket vorangehenden ersten Paketes ist.
4. Verfahren nach den Ansprüchen 2 und 3, dadurch gekennzeichnet, daß ein zweites Paket in der Emp-



fangsstation (IWU2) verworfen wird, wenn seine zweite Sequenznummer kleiner/größer als die vorbestimmte erste Sequenznummer eines vorher empfangenen ersten Paketes ist.

5. Verfahren nach den Ansprüchen 2 und 3, dadurch gekennzeichnet, daß empfangene zweite Pakete, welche eine gleiche zweite Sequenznummer besitzen, die größer/kleiner ist als die vorbestimmte erste Sequenznummer des vorher empfangenen ersten Paketes, bis zum Empfangen eines ersten Paketes gepuffert werden, das eine vorbestimmte erste Sequenznummer besitzt, die gleich der zweiten Sequenznummer der auf diese Weise gepufferten zweiten Pakete ist.

6. Verfahren nach den Ansprüchen 2 und 3, dadurch gekennzeichnet, daß beim Empfangen in der Empfangsstation (IWU2) von einem der von der Sendestation (IWU1) kommenden ersten Pakete das erste Paket gepuffert wird, wenn seine vorbestimmte erste Sequenznummer größer/kleiner ist als die Sequenznummer des letzten vorher empfangenen und nicht gepufferten Paketes, die um einen vorbestimmten Wert erhöht/vermindert wurde, daß beim Empfangen durch die Empfangsstation (IWU2) von einem der von der Sendestation (IWU1) kommenden zweiten Pakete das zweite Paket gepuffert wird, wenn seine zweite Sequenznummer größer/Meiner ist als die Sequenznummer des letzten vorher empfangenen und nicht gepufferten Paketes, daß beim Empfangen durch die Empfangsstation (IWU2) eines zweiten Paketes, dessen zweite Sequenznummer gleich der Sequenznummer des letzten vorher empfangenen und nicht gepufferten Paketes ist, die um den vorbestimmten Wert erhöht/vermindert wurde, das Paket zu einem Ausgangsanschluß (R) der Empfangsstation (IWU2) weitergeleitet wird, diese bereits gepufferten ersten Pakete, deren erste Sequenznummern zusammen mit der Sequenznummer des weitergeleiteten ersten Paketes einen Teil der monotonen Reihe bilden, ebenfalls zu dem Ausgangsanschluß (R) in aufsteigender/absteigender Reihenfolge ihrer ersten Sequenznummer weitergeleitet werden, und zwar zusammen mit den zweiten Paketen, deren zweite Sequenznummer gleich einem zuvor weitergeleiteten Paket ist, und daß beim Empfangen eines zweiten Paketes, dessen zweite Sequenznummer kleiner/größer ist als die Sequenznummer des letzten vorher empfangenen und nicht gepufferten Paketes oder eines ersten Paketes, dessen vorbestimmte erste Sequenznummer kleiner/größer ist als die Sequenznummer des letzten vorher

empfangenen und nicht gepufferten Paketes, die um den vorbestimmten Wert erhöht/vermindert ist, das Paket verworfen wird.

7. Verfahren nach Anspruch 6, dadurch gekennzeichnet, daß ein Zeitgeber für jedes einzelne der gepufferten Pakete gestartet wird, alle gepufferten Pakete, deren Sequenznummer kleiner/größer ist als die Sequenznummer dieses einen Paketes, und alle gepufferten Pakete, deren Sequenznummer größer/kleiner ist als die Sequenznummer dieses einen Paketes und welche mit diesem einen Paket einen Teil der monotonen Reihe bilden, zu dem Ausgangsanschluß (R) weitergeleitet werden, und zwar nachdem sie sequentiell geordnet wurden, um eine Reihe von Paketen zu bilden, die zu der monotonen Reihe in vorbestimmter Weise in Beziehung steht, wenn der Zeitgeber (T) einen vorbestimmten Wert erreicht.

8. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß in dem Netz (SMDS) die zweiten Pakete eine individuelle Bestimmungsadresse besitzen und von der Sendestation (IWU1) an die Empfangsstation (IWU2) gesendet werden, und die ersten Pakete eine Gruppen-Bestimmungsadresse besitzen und von der Sendestation (IWU1) an die Empfangsstation (IWU2) und an mindestens eine weitere Empfangsstation (IWU3, IWU4) gesendet werden.

9. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß der zweiten Sequenznummer aller zweiten Pakete, welche vor dem Senden von irgendeinem ersten Paket gesendet werden, ein vorbestimmter Anfangswert zugewiesen wird.

10. Sequentielle Rückordnungsvorrichtung zum sequentiellen Rückordnen von Informationspaketen eines Informationspaketstromes (Min), der über ein Netz (SMDS) von einer Sendestation (IWU1) zu einer Empfangsstation (IWU2) gesendet wird und durch Sequenznummern identifiziert ist, dadurch gekennzeichnet, daß für erste Pakete, die im Informationspaketstrom (Min) enthalten sind und in der Empfangsstation (IWU2) nicht mehr sequentiell geordnet empfangen werden, und zwar bezüglich zueinander oder bezüglich zweiter Pakete, welche immer sequentiell geordnet empfangen werden, die sequentielle Rückordnungsvorrichtung beinhaltet:

- eine Sequenznummern-Zuordnungseinrichtung (P1, C1), welche sich in der Sendestation (IWU1) befindet und geeignet ist, vorbestimmte erste Sequenznummern den ersten Paketen zuzuordnen und jedem auf ein erstes Paket folgenden zweiten Paket eine zweite Sequenznummer zuzuordnen, welche zur diesem

- ersten Paket zugewiesenen vorbestimmten ersten Sequenznummer eine vorbestimmte Beziehung besitzt; und
- eine sequentielle Rückordnungseinrichtung (P2, B, C2, T), welche sich in der Empfangsstation (IWU2) befindet und geeignet ist, die ersten und zweiten Pakete gemäß ihrer ersten bzw. zweiten Sequenznummern sequentiell rückzuordnen.
11. Verfahren nach Anspruch 10, dadurch gekennzeichnet, daß die den ersten Paketen zugeordneten vorbestimmten ersten Sequenznummern eine zunehmende/abnehmende monotone Reihe bilden.
  12. Verfahren nach Anspruch 10, dadurch gekennzeichnet, daß die dem zweiten Paket zugeordnete zweite Sequenznummer gleich der vorbestimmten ersten Sequenznummer des dem zweiten Paket vorangehenden ersten Paketes ist.
  13. Sequentielle Rückordnungsvorrichtung nach den Ansprüchen 11 und 12, dadurch gekennzeichnet, daß die Sequenznummern-Zuordnungseinrichtung (P1, C1) eine Zählleinrichtung (C1) beinhaltet, die geeignet ist, einen Zählwert zu liefern, und eine Verarbeitungseinrichtung (P1), welche geeignet ist, diesen Zählwert den zweiten zu sendenden Paketen zuzuweisen und geeignet ist, die Zählleinrichtung so zu steuern, daß sie um einen vorbestimmten Wert erhöht/vermindert wird, bevor der Zählwert den zu sendenden ersten Paketen zugewiesen wird.
  14. Sequentielle Rückordnungsvorrichtung nach den Ansprüchen 11 und 12, dadurch gekennzeichnet, daß die sequentielle Rückordnungseinrichtung (P2, B, C2, T) eine Puffereinrichtung (B) beinhaltet, welche geeignet ist, zweite empfangene Pakete, die eine gleiche zweite Sequenznummer besitzen, welche größer/kleiner ist als die Sequenznummer des letzten vorher empfangenen und nicht gepufferten Paketes, zu puffern, bis ein erstes Paket empfangen wird, welches eine vorbestimmte erste Sequenznummer besitzt, die gleich der zweiten Sequenznummer der auf diese Weise gepufferten zweiten Pakete ist.
  15. Sequentielle Rückordnungsvorrichtung nach den Ansprüchen 13 und 14, dadurch gekennzeichnet, daß die sequentielle Rückordnungseinrichtung (P2, B, C2, T) mindestens eine zweite Zählleinrichtung (C2) beinhaltet, welche einen zweiten Zählwert liefert, deren Anfangswert beim Hochfahren der sequentiellen Rückordnungseinrichtung gleich dem Anfangswert der ersten Zählleinrichtung (C1) ist,

und eine zweite Verarbeitungseinrichtung (P2), welche beim Empfangen von einem der ersten Pakete von der Sendestation (IWU1) geeignet ist, das erste Paket in der Puffereinrichtung (B) zu puffern, wenn dessen vorbestimmte erste Sequenznummer größer/kleiner ist als der um den vorbestimmten Wert erhöhte/verminderte zweite Zählwert, welche beim Empfangen eines der zweiten Pakete von der Sendestation (IWU1) geeignet ist, das zweite Paket in der Puffereinrichtung (B) zu puffern, wenn dessen zweite Sequenznummer größer/kleiner ist als der zweite Zählwert, welche beim Empfangen eines zweiten Paketes, dessen zweite Sequenznummer gleich dem zweiten Zählwert ist, oder beim Empfangen eines ersten Paketes mit einer vorbestimmten ersten Sequenznummer, die gleich dem um den vorbestimmten Wert erhöhten/verminderten zweiten Zählwert ist, geeignet ist, das Paket an einen Ausgangsanschluß (R) der sequentiellen Rückordnungseinrichtung weiterzuleiten und die zweite Zählleinrichtung (C2) so zu steuern, daß sie um den vorbestimmten Wert erhöht/vermindert wird, wenn ein erstes Paket an den Ausgangsanschluß (R) weitergeleitet wird, wobei diese bereits gepufferten ersten Pakete, deren erste Sequenznummern zusammen mit der ersten Sequenznummer des ersten weitergeleiteten Paketes einen Teil der monotonen Reihe bilden, und diese zweiten Pakete, deren zweite Sequenznummer gleich der Sequenznummer von entweder den weitergeleiteten oder von einem dieser gepufferten ersten Pakete ist, dann ebenfalls an den Ausgangsanschluß (R) weitergeleitet wird, derart, daß diese gepufferten ersten Pakete in aufsteigender/absteigender Reihenfolge ihrer Sequenznummer sequentiell geordnet werden, zusammen mit gepufferten zweiten Paketen, die bezüglich den weitergeleiteten ersten Paketen derart sequentiell geordnet sind, daß sie auf ein erstes Paket folgen, welches die gleiche vorbestimmte erste Sequenznummer wie diese zweite Sequenznummer besitzt, und welche, beim Empfangen eines zweiten Paketes, dessen zweite Sequenznummer kleiner/größer als dieser Zählwert ist, oder beim Empfangen eines ersten Paketes, dessen vorbestimmte erste Sequenznummer kleiner/größer als der um den vorbestimmten Wert erhöhte/verminderte Zählwert ist, geeignet ist, dieses Paket zu verwerfen.

16. Sequentielle Rückordnungsvorrichtung nach Anspruch 15, dadurch gekennzeichnet, daß die sequentielle Rückordnungseinrichtung einen Zeitgebereinrichtung (T) beinhaltet, die von der zweiten Verarbeitungseinrichtung (P2) gesteuert wird, welche geeignet ist, einen Zeitgeber für jedes einzelne der gepufferten Pakete zu starten, wobei alle gepufferten Pakete, deren Sequenznummer kleiner/größer ist als die Sequenznummer dieses

einen Paketes, und alle gepufferten Pakete, deren Sequenznummer größer/kleiner als die Sequenznummer von diesem einen Paket ist und welche mit diesem einen Paket einen Teil der monotonen Reihe bilden, zu dem Ausgangsanschluß (R) weitergeleitet werden, und zwar nachdem sie sequentiell geordnet wurden, um eine Reihe von Paketen zu bilden, die zu der monotonen Reihe in vorbestimmter Weise in Beziehung steht, wenn der Zeitgeber (T) einen vorbestimmten Wert erreicht.

17. Sequentielle Rückordnungsvorrichtung nach Anspruch 10, dadurch gekennzeichnet, daß in dem Netz (SMDS) die zweiten Pakete eine individuelle Bestimmungsadresse besitzen und von der Sendestation (IWU1) an die Empfangsstation (IWU2) gesendet werden, und die ersten Pakete eine Gruppen-Bestimmungsadresse besitzen und von der Sendestation (IWU1) an die Empfangsstation (IWU2) und an mindestens eine weitere Empfangsstation (IWU3, IWU4) gesendet werden.

#### Revendications

1. Procédé de remise en séquence de paquets d'informations d'un courant de paquets d'informations (Min) transmis depuis une station émettrice (IWU1) vers une station réceptrice (IWU2) sur un réseau (SMDS) et identifiés par des numéros de séquence, caractérisé en ce que, pour les premiers paquets inclus dans ledit courant de paquets d'informations (Min) et reçus dans ladite station réceptrice (IWU2) hors séquence les uns par rapport aux autres ou par rapport à des deuxièmes paquets qui sont toujours reçus en séquence, ledit procédé comporte les étapes consistant à :
  - dans ladite station émettrice (IWU1), allouer des premiers numéros de séquence prédéterminés auxdits premiers paquets et allouer à chaque deuxième paquet suivant un premier paquet, un deuxième numéro de séquence qui est lié selon une relation prédéterminée au premier numéro de séquence prédéterminé alloué à ce premier paquet ; et
  - dans ladite station réceptrice (IWU2), remettre en séquence lesdits premiers et deuxièmes paquets, respectivement en fonction de leurs premiers et deuxièmes numéros de séquence.
2. Procédé selon la revendication 1, caractérisé en ce que lesdits premiers numéros de séquence prédéterminés alloués auxdits premiers paquets forment une série monotone croissante/décroissante.
3. Procédé selon la revendication 1, caractérisé en ce que ledit deuxième numéro de séquence alloué audit deuxième paquet est égal au premier numéro

de séquence prédéterminé du premier paquet précédant ledit deuxième paquet.

4. Procédé selon les revendications 2 et 3, caractérisé en ce qu'un deuxième paquet est éliminé dans ladite station réceptrice (IWU2) lorsque son dit deuxième numéro de séquence est inférieur/supérieur au premier numéro de séquence prédéterminé d'un premier paquet précédemment reçu.
5. Procédé selon les revendications 2 et 3, caractérisé en ce que les deuxièmes paquets reçus ayant un même deuxième numéro de séquence supérieur/inférieur au premier numéro de séquence prédéterminé du premier paquet précédemment reçu sont retenus jusqu'à réception d'un premier paquet ayant un premier numéro de séquence prédéterminé égal au deuxième numéro de séquence des deuxièmes paquets ainsi retenus.
6. Procédé selon les revendications 2 et 3, caractérisé en ce que, lors de la réception dans ladite station réceptrice (IWU2) de l'un desdits premiers paquets depuis ladite station émettrice (IWU1), ledit premier paquet est retenu lorsque son premier numéro de séquence prédéterminé est supérieur/inférieur au numéro de séquence du dernier paquet précédemment reçu et non retenu incrémenté/décroché d'une valeur prédéterminée, en ce que lors de la réception par ladite station réceptrice (IWU2) de l'un desdits deuxièmes paquets depuis ladite station émettrice (IWU1), ledit deuxième paquet est retenu lorsque son deuxième numéro de séquence est supérieur/inférieur au numéro de séquence du dernier paquet précédemment reçu et non retenu, en ce que lors de la réception par ladite station réceptrice (IWU2) d'un deuxième paquet avec un dit deuxième numéro de séquence égal au numéro de séquence du dernier paquet précédemment reçu et non retenu ou d'un premier paquet avec un dit numéro de séquence prédéterminé égal au numéro de séquence du dernier paquet précédemment reçu et non retenu incrémenté/décroché de ladite valeur prédéterminée, ledit paquet est transmis à une borne de sortie (R) de ladite station réceptrice (IWU2), ces premiers paquets déjà retenus, dont les premiers numéros de séquence avec le numéro de séquence du premier paquet transmis font partie de ladite série monotone également transmis à ladite borne de sortie (R), en ordre ascendant/descendant de leurs premiers numéros de séquence, ainsi que les deuxièmes paquets ayant un dit deuxième numéro de séquence égal à un paquet précédemment transmis et en ce que lors de la réception d'un dit deuxième paquet ayant un dit deuxième numéro de séquence inférieur/supérieur au numéro de séquence du dernier paquet précédemment reçu et non retenu ou d'un

premier paquet ayant un premier numéro de séquence prédéterminé inférieur/supérieur au numéro de séquence du dernier paquet précédemment reçu et non retenu incrémenté/décroché de ladite valeur prédéterminée, ledit paquet est éliminé.

7. Procédé selon la revendication 6, caractérisé en ce qu'un séquenceur est démarré pour chacun desdits paquets retenus, tous les paquets retenus avec un numéro de séquence inférieur/supérieur au numéro de séquence dudit premier paquet et tous les paquets retenus avec un numéro de séquence supérieur/inférieur au numéro de séquence dudit premier paquet et qui, avec ledit premier paquet, font partie de ladite série monotone, transmise à ladite borne de sortie (R) après avoir été séquencés de manière à former une série de paquets liée à ladite série monotone d'une manière prédéterminée, lorsque ledit séquenceur atteint une valeur prédéterminée.
8. Procédé selon la revendication 1, caractérisé en ce que dans ledit réseau (SMDS), lesdits deuxièmes paquets ont une adresse de destination individuelle et sont envoyés de ladite station émettrice (IWU1) à ladite station réceptrice (IWU2) et lesdits premiers paquets ont une adresse de destination de groupe et sont envoyés de ladite station émettrice (IWU1) à ladite station réceptrice (IWU2) et à au moins une autre station réceptrice (IWU3, IWU4).
9. Procédé selon la revendication 1, caractérisé en ce qu'une valeur initiale prédéterminée est assignée au deuxième numéro de séquence de l'ensemble des deuxièmes paquets qui sont transmis avant la transmission d'un quelconque premier paquet.
10. Dispositif de remise en séquence pour remettre en séquence des paquets d'informations d'un courant de paquets d'informations (Min) transmis d'une station émettrice (IWU1) à une station réceptrice (IWU2) sur un réseau (SMDS) et identifiés par des numéros de séquence, caractérisé en ce que, pour des premiers paquets inclus dans ledit courant de paquets d'informations (Min) qui sont reçus dans ladite station réceptrice (IWU2) hors séquence les uns par rapport aux autres ou par rapport aux deuxièmes paquets qui sont toujours reçus en séquence, ledit dispositif de remise en séquence comporte :
  - des moyens d'allocations de numéros de séquence (P1, C1) situés dans ladite station émettrice (IWU1) et qui sont adaptés pour allouer des premiers numéros de séquence prédéterminés auxdits premiers paquets et allouer à chaque deuxième paquet suivant un

premier paquet, un deuxième numéro de séquence qui est lié selon une relation prédéterminée au premier numéro de séquence prédéterminé alloué à ce premier paquet ; et

- des moyens de remise en séquence (P2, B, C2, T) situés dans ladite station réceptrice (IWU2) et qui sont adaptés pour remettre en séquence lesdits premiers et deuxièmes paquets respectivement en fonction de leurs premiers et deuxièmes numéros de séquence.
11. Dispositif de remise en séquence selon la revendication 10, caractérisé en ce que lesdits premiers numéros de séquence prédéterminés alloués auxdits premiers paquets forment une série monotone croissante/décroissante.
  12. Dispositif de remise en séquence selon la revendication 10, caractérisé en ce que ledit deuxième numéro de séquence alloué audit deuxième paquet est égal au premier numéro de séquence prédéterminé du premier paquet précédent ledit deuxième paquet.
  13. Dispositif de remise en séquence selon les revendications 11 et 12, caractérisé en ce que lesdits moyens d'allocations de numéro de séquence (P1, C1) comportent des moyens formant compteur et des moyens de traitement (P1) adaptés pour assigner ladite valeur de compteur auxdits deuxièmes paquets à transmettre et adaptés pour contrôler lesdits moyens formant compteur pour être incrémentés/décrochés d'une valeur prédéterminée avant d'assigner ladite valeur de compteur auxdits premiers paquets à transmettre.
  14. Dispositif de remise en séquence selon les revendications 11 et 12, caractérisé en ce que lesdits moyens de remise en séquence (P2, B, C2, T) comportent des moyens de retenue (B) adaptés pour retenir les deuxièmes paquets reçus ayant un deuxième numéro de séquence qui est supérieur/inférieur au numéro de séquence du dernier paquet précédemment reçu et non retenu jusqu'à réception d'un premier paquet ayant un premier numéro de séquence prédéterminé égal au deuxième numéro de séquence des deuxièmes paquets ainsi retenus.
  15. Dispositif de remise en séquence selon les revendications 13 et 14, caractérisé en ce que lesdits moyens de remise en séquence (P2, B, C2, T) comportent au moins des deuxièmes moyens formant compteur (C2) fournissant une deuxième valeur de compteur dont la valeur initiale est, au démarrage desdits moyens de remise en séquence, rendue

égale à la valeur initiale dudit premier compteur (C1) et des deuxièmes moyens de traitement (P2) qui, lors de la réception de l'un desdits premiers paquets depuis ladite station émettrice (IWU1), sont adaptés pour retenir ledit premier paquet dans lesdits moyens de retenue (B) lorsque son premier numéro de séquence prédéterminé est supérieur/inférieur à ladite deuxième valeur de compteur 5  
 10  
 15  
 20  
 25  
 30  
 35  
 40  
 45  
 50  
 55  
 60  
 65  
 70  
 75  
 80  
 85  
 90  
 95  
 100  
 105  
 110  
 115  
 120  
 125  
 130  
 135  
 140  
 145  
 150  
 155  
 160  
 165  
 170  
 175  
 180  
 185  
 190  
 195  
 200  
 205  
 210  
 215  
 220  
 225  
 230  
 235  
 240  
 245  
 250  
 255  
 260  
 265  
 270  
 275  
 280  
 285  
 290  
 295  
 300  
 305  
 310  
 315  
 320  
 325  
 330  
 335  
 340  
 345  
 350  
 355  
 360  
 365  
 370  
 375  
 380  
 385  
 390  
 395  
 400  
 405  
 410  
 415  
 420  
 425  
 430  
 435  
 440  
 445  
 450  
 455  
 460  
 465  
 470  
 475  
 480  
 485  
 490  
 495  
 500  
 505  
 510  
 515  
 520  
 525  
 530  
 535  
 540  
 545  
 550  
 555  
 560  
 565  
 570  
 575  
 580  
 585  
 590  
 595  
 600  
 605  
 610  
 615  
 620  
 625  
 630  
 635  
 640  
 645  
 650  
 655  
 660  
 665  
 670  
 675  
 680  
 685  
 690  
 695  
 700  
 705  
 710  
 715  
 720  
 725  
 730  
 735  
 740  
 745  
 750  
 755  
 760  
 765  
 770  
 775  
 780  
 785  
 790  
 795  
 800  
 805  
 810  
 815  
 820  
 825  
 830  
 835  
 840  
 845  
 850  
 855  
 860  
 865  
 870  
 875  
 880  
 885  
 890  
 895  
 900  
 905  
 910  
 915  
 920  
 925  
 930  
 935  
 940  
 945  
 950  
 955  
 960  
 965  
 970  
 975  
 980  
 985  
 990  
 995  
 1000  
 1005  
 1010  
 1015  
 1020  
 1025  
 1030  
 1035  
 1040  
 1045  
 1050  
 1055  
 1060  
 1065  
 1070  
 1075  
 1080  
 1085  
 1090  
 1095  
 1100  
 1105  
 1110  
 1115  
 1120  
 1125  
 1130  
 1135  
 1140  
 1145  
 1150  
 1155  
 1160  
 1165  
 1170  
 1175  
 1180  
 1185  
 1190  
 1195  
 1200  
 1205  
 1210  
 1215  
 1220  
 1225  
 1230  
 1235  
 1240  
 1245  
 1250  
 1255  
 1260  
 1265  
 1270  
 1275  
 1280  
 1285  
 1290  
 1295  
 1300  
 1305  
 1310  
 1315  
 1320  
 1325  
 1330  
 1335  
 1340  
 1345  
 1350  
 1355  
 1360  
 1365  
 1370  
 1375  
 1380  
 1385  
 1390  
 1395  
 1400  
 1405  
 1410  
 1415  
 1420  
 1425  
 1430  
 1435  
 1440  
 1445  
 1450  
 1455  
 1460  
 1465  
 1470  
 1475  
 1480  
 1485  
 1490  
 1495  
 1500  
 1505  
 1510  
 1515  
 1520  
 1525  
 1530  
 1535  
 1540  
 1545  
 1550  
 1555  
 1560  
 1565  
 1570  
 1575  
 1580  
 1585  
 1590  
 1595  
 1600  
 1605  
 1610  
 1615  
 1620  
 1625  
 1630  
 1635  
 1640  
 1645  
 1650  
 1655  
 1660  
 1665  
 1670  
 1675  
 1680  
 1685  
 1690  
 1695  
 1700  
 1705  
 1710  
 1715  
 1720  
 1725  
 1730  
 1735  
 1740  
 1745  
 1750  
 1755  
 1760  
 1765  
 1770  
 1775  
 1780  
 1785  
 1790  
 1795  
 1800  
 1805  
 1810  
 1815  
 1820  
 1825  
 1830  
 1835  
 1840  
 1845  
 1850  
 1855  
 1860  
 1865  
 1870  
 1875  
 1880  
 1885  
 1890  
 1895  
 1900  
 1905  
 1910  
 1915  
 1920  
 1925  
 1930  
 1935  
 1940  
 1945  
 1950  
 1955  
 1960  
 1965  
 1970  
 1975  
 1980  
 1985  
 1990  
 1995  
 2000  
 2005  
 2010  
 2015  
 2020  
 2025  
 2030  
 2035  
 2040  
 2045  
 2050  
 2055  
 2060  
 2065  
 2070  
 2075  
 2080  
 2085  
 2090  
 2095  
 2100  
 2105  
 2110  
 2115  
 2120  
 2125  
 2130  
 2135  
 2140  
 2145  
 2150  
 2155  
 2160  
 2165  
 2170  
 2175  
 2180  
 2185  
 2190  
 2195  
 2200  
 2205  
 2210  
 2215  
 2220  
 2225  
 2230  
 2235  
 2240  
 2245  
 2250  
 2255  
 2260  
 2265  
 2270  
 2275  
 2280  
 2285  
 2290  
 2295  
 2300  
 2305  
 2310  
 2315  
 2320  
 2325  
 2330  
 2335  
 2340  
 2345  
 2350  
 2355  
 2360  
 2365  
 2370  
 2375  
 2380  
 2385  
 2390  
 2395  
 2400  
 2405  
 2410  
 2415  
 2420  
 2425  
 2430  
 2435  
 2440  
 2445  
 2450  
 2455  
 2460  
 2465  
 2470  
 2475  
 2480  
 2485  
 2490  
 2495  
 2500  
 2505  
 2510  
 2515  
 2520  
 2525  
 2530  
 2535  
 2540  
 2545  
 2550  
 2555  
 2560  
 2565  
 2570  
 2575  
 2580  
 2585  
 2590  
 2595  
 2600  
 2605  
 2610  
 2615  
 2620  
 2625  
 2630  
 2635  
 2640  
 2645  
 2650  
 2655  
 2660  
 2665  
 2670  
 2675  
 2680  
 2685  
 2690  
 2695  
 2700  
 2705  
 2710  
 2715  
 2720  
 2725  
 2730  
 2735  
 2740  
 2745  
 2750  
 2755  
 2760  
 2765  
 2770  
 2775  
 2780  
 2785  
 2790  
 2795  
 2800  
 2805  
 2810  
 2815  
 2820  
 2825  
 2830  
 2835  
 2840  
 2845  
 2850  
 2855  
 2860  
 2865  
 2870  
 2875  
 2880  
 2885  
 2890  
 2895  
 2900  
 2905  
 2910  
 2915  
 2920  
 2925  
 2930  
 2935  
 2940  
 2945  
 2950  
 2955  
 2960  
 2965  
 2970  
 2975  
 2980  
 2985  
 2990  
 2995  
 3000  
 3005  
 3010  
 3015  
 3020  
 3025  
 3030  
 3035  
 3040  
 3045  
 3050  
 3055  
 3060  
 3065  
 3070  
 3075  
 3080  
 3085  
 3090  
 3095  
 3100  
 3105  
 3110  
 3115  
 3120  
 3125  
 3130  
 3135  
 3140  
 3145  
 3150  
 3155  
 3160  
 3165  
 3170  
 3175  
 3180  
 3185  
 3190  
 3195  
 3200  
 3205  
 3210  
 3215  
 3220  
 3225  
 3230  
 3235  
 3240  
 3245  
 3250  
 3255  
 3260  
 3265  
 3270  
 3275  
 3280  
 3285  
 3290  
 3295  
 3300  
 3305  
 3310  
 3315  
 3320  
 3325  
 3330  
 3335  
 3340  
 3345  
 3350  
 3355  
 3360  
 3365  
 3370  
 3375  
 3380  
 3385  
 3390  
 3395  
 3400  
 3405  
 3410  
 3415  
 3420  
 3425  
 3430  
 3435  
 3440  
 3445  
 3450  
 3455  
 3460  
 3465  
 3470  
 3475  
 3480  
 3485  
 3490  
 3495  
 3500  
 3505  
 3510  
 3515  
 3520  
 3525  
 3530  
 3535  
 3540  
 3545  
 3550  
 3555  
 3560  
 3565  
 3570  
 3575  
 3580  
 3585  
 3590  
 3595  
 3600  
 3605  
 3610  
 3615  
 3620  
 3625  
 3630  
 3635  
 3640  
 3645  
 3650  
 3655  
 3660  
 3665  
 3670  
 3675  
 3680  
 3685  
 3690  
 3695  
 3700  
 3705  
 3710  
 3715  
 3720  
 3725  
 3730  
 3735  
 3740  
 3745  
 3750  
 3755  
 3760  
 3765  
 3770  
 3775  
 3780  
 3785  
 3790  
 3795  
 3800  
 3805  
 3810  
 3815  
 3820  
 3825  
 3830  
 3835  
 3840  
 3845  
 3850  
 3855  
 3860  
 3865  
 3870  
 3875  
 3880  
 3885  
 3890  
 3895  
 3900  
 3905  
 3910  
 3915  
 3920  
 3925  
 3930  
 3935  
 3940  
 3945  
 3950  
 3955  
 3960  
 3965  
 3970  
 3975  
 3980  
 3985  
 3990  
 3995  
 4000  
 4005  
 4010  
 4015  
 4020  
 4025  
 4030  
 4035  
 4040  
 4045  
 4050  
 4055  
 4060  
 4065  
 4070  
 4075  
 4080  
 4085  
 4090  
 4095  
 4100  
 4105  
 4110  
 4115  
 4120  
 4125  
 4130  
 4135  
 4140  
 4145  
 4150  
 4155  
 4160  
 4165  
 4170  
 4175  
 4180  
 4185  
 4190  
 4195  
 4200  
 4205  
 4210  
 4215  
 4220  
 4225  
 4230  
 4235  
 4240  
 4245  
 4250  
 4255  
 4260  
 4265  
 4270  
 4275  
 4280  
 4285  
 4290  
 4295  
 4300  
 4305  
 4310  
 4315  
 4320  
 4325  
 4330  
 4335  
 4340  
 4345  
 4350  
 4355  
 4360  
 4365  
 4370  
 4375  
 4380  
 4385  
 4390  
 4395  
 4400  
 4405  
 4410  
 4415  
 4420  
 4425  
 4430  
 4435  
 4440  
 4445  
 4450  
 4455  
 4460  
 4465  
 4470  
 4475  
 4480  
 4485  
 4490  
 4495  
 4500  
 4505  
 4510  
 4515  
 4520  
 4525  
 4530  
 4535  
 4540  
 4545  
 4550  
 4555  
 4560  
 4565  
 4570  
 4575  
 4580  
 4585  
 4590  
 4595  
 4600  
 4605  
 4610  
 4615  
 4620  
 4625  
 4630  
 4635  
 4640  
 4645  
 4650  
 4655  
 4660  
 4665  
 4670  
 4675  
 4680  
 4685  
 4690  
 4695  
 4700  
 4705  
 4710  
 4715  
 4720  
 4725  
 4730  
 4735  
 4740  
 4745  
 4750  
 4755  
 4760  
 4765  
 4770  
 4775  
 4780  
 4785  
 4790  
 4795  
 4800  
 4805  
 4810  
 4815  
 4820  
 4825  
 4830  
 4835  
 4840  
 4845  
 4850  
 4855  
 4860  
 4865  
 4870  
 4875  
 4880  
 4885  
 4890  
 4895  
 4900  
 4905  
 4910  
 4915  
 4920  
 4925  
 4930  
 4935  
 4940  
 4945  
 4950  
 4955  
 4960  
 4965  
 4970  
 4975  
 4980  
 4985  
 4990  
 4995  
 5000  
 5005  
 5010  
 5015  
 5020  
 5025  
 5030  
 5035  
 5040  
 5045  
 5050  
 5055  
 5060  
 5065  
 5070  
 5075  
 5080  
 5085  
 5090  
 5095  
 5100  
 5105  
 5110  
 5115  
 5120  
 5125  
 5130  
 5135  
 5140  
 5145  
 5150  
 5155  
 5160  
 5165  
 5170  
 5175  
 5180  
 5185  
 5190  
 5195  
 5200  
 5205  
 5210  
 5215  
 5220  
 5225  
 5230  
 5235  
 5240  
 5245  
 5250  
 5255  
 5260  
 5265  
 5270  
 5275  
 5280  
 5285  
 5290  
 5295  
 5300  
 5305  
 5310  
 5315  
 5320  
 5325  
 5330  
 5335  
 5340  
 5345  
 5350  
 5355  
 5360  
 5365  
 5370  
 5375  
 5380  
 5385  
 5390  
 5395  
 5400  
 5405  
 5410  
 5415  
 5420  
 5425  
 5430  
 5435  
 5440  
 5445  
 5450  
 5455  
 5460  
 5465  
 5470  
 5475  
 5480  
 5485  
 5490  
 5495  
 5500  
 5505  
 5510  
 5515  
 5520  
 5525  
 5530  
 5535  
 5540  
 5545  
 5550  
 5555  
 5560  
 5565  
 5570  
 5575  
 5580  
 5585  
 5590  
 5595  
 5600  
 5605  
 5610  
 5615  
 5620  
 5625  
 5630  
 5635  
 5640  
 5645  
 5650  
 5655  
 5660  
 5665  
 5670  
 5675  
 5680  
 5685  
 5690  
 5695  
 5700  
 5705  
 5710  
 5715  
 5720  
 5725  
 5730  
 5735  
 5740  
 5745  
 5750  
 5755  
 5760  
 5765  
 5770  
 5775  
 5780  
 5785  
 5790  
 5795  
 5800  
 5805  
 5810  
 5815  
 5820  
 5825  
 5830  
 5835  
 5840  
 5845  
 5850  
 5855  
 5860  
 5865  
 5870  
 5875  
 5880  
 5885  
 5890  
 5895  
 5900  
 5905  
 5910  
 5915  
 5920  
 5925  
 5930  
 5935  
 5940  
 5945  
 5950  
 5955  
 5960  
 5965  
 5970  
 5975  
 5980  
 5985  
 5990  
 5995  
 6000  
 6005  
 6010  
 6015  
 6020  
 6025  
 6030  
 6035  
 6040  
 6045  
 6050  
 6055  
 6060  
 6065  
 6070  
 6075  
 6080  
 6085  
 6090  
 6095  
 6100  
 6105  
 6110  
 6115  
 6120  
 6125  
 6130  
 6135  
 6140  
 6145  
 6150  
 6155  
 6160  
 6165  
 6170  
 6175  
 6180  
 6185  
 6190  
 6195  
 6200  
 6205  
 6210  
 6215  
 6220  
 6225  
 6230  
 6235  
 6240  
 6245  
 6250  
 6255  
 6260  
 6265  
 6270  
 6275  
 6280  
 6285  
 6290  
 6295  
 6300  
 6305  
 6310  
 6315  
 6320  
 6325  
 6330  
 6335  
 6340  
 6345  
 6350  
 6355  
 6360  
 6365  
 6370  
 6375  
 6380  
 6385  
 6390  
 6395  
 6400  
 6405  
 6410  
 6415  
 6420  
 6425  
 6430  
 6435  
 6440  
 6445  
 6450  
 6455  
 6460  
 6465  
 6470  
 6475  
 6480  
 6485  
 6490  
 6495  
 6500  
 6505  
 6510  
 6515  
 6520  
 6525  
 6530  
 6535  
 6540  
 6545  
 6550  
 6555  
 6560  
 6565  
 6570  
 6575  
 6580  
 6585  
 6590  
 6595  
 6600  
 6605  
 6610  
 6615  
 6620  
 6625  
 6630  
 6635  
 6640  
 6645  
 6650  
 6655  
 6660  
 6665  
 6670  
 6675  
 6680  
 6685  
 6690  
 6695  
 6700  
 6705  
 6710  
 6715  
 6720  
 6725  
 6730  
 6735  
 6740  
 6745  
 6750  
 6755  
 6760  
 6765  
 6770  
 6775  
 6780  
 6785  
 6790  
 6795  
 6800  
 6805  
 6810  
 6815  
 6820  
 6825  
 6830  
 6835  
 6840  
 6845  
 6850  
 6855  
 6860  
 6865  
 6870  
 68

